



PP505

Anti-graffiti Coating Extra Strong

Generally:

Pica Protector 505 is a wax based water borne anti-graffiti coating system that protects the surface effectively against spray, paintbrush and Marker Pen graffiti. Pica Protector 505's unique formula gives you the same amount of graffiti protection with just one layer that ordinary Protective Coatings give with two layers.

Use:

Pica Protector 505 can be used on most types of surfaces. Recommended surface temperature:
+40 - +5 ° centigrade.

Directions for use:

Application

-Clean surface thoroughly.
-Coat surface evenly with Pica Protector 505. Work from the bottom of the facade to the top of the facade. The facade is now effectively protected.

Cleaning

- Remove the graffiti with a high pressure cleaner at 70 bar at a temperature of 70 ° Celsius.

- Re-protect with one to two coatings of Pica Protector 505.

Solution to be used:

Concentrate (pH 8,5).

Estimated amount to be used:

Varies according to the surface. In General estimate the following;

Painted surfaces, natural stone	0,10L/m ²
Concrete, Brick	0,15L/m ²
Render	0,20L/m ²

Personal protective measures:

Not needed.

Labelling:

Not classified as hazardous goods.

Storage/durability:

Store dark and frost free. Durability, about 24 months in sealed original container.

Technical data:

Contains:	Montan waxes
Appearance:	Milky white liquid
Odour:	Neutral

The information supplied is only intended to be used as a guideline. Pica Kemi AB therefore accepts no liability based on this information on behalf of the user.

Pica AB
Kabingatan 13, S-212 39 MALMÖ
Tel. +46-40-18 58 20 Fax.+46-40-18 58 23
Hemsida: www.picakemi.se