



PP 500

Anti-graffiti coating

Generally:

Pica Protector 500 is a wax based water borne graffiti protection system that protects the surface effectively against spray, paintbrush and Indian ink graffiti. Pica Protector 500 is a sacrificial protection system, which means that the surface must be re-protected since the protective coating disappears, wholly or partially, during high pressure cleaning.

Use:

Pica Protector 500 can be used on most types of surfaces. Recommended surface temperature: +40 - +5 ° centigrade.

Directions for use:

Application

- Clean surface thoroughly.
- Coat surface evenly with Pica Protector 500. Work from the bottom of the facade to the top of the facade.
- Coat surface with an additional coating when the first coating has become transparent. The surface is now effectively protected. NB. Always apply two coatings to get fully adequate protection.

Cleaning

- Remove the graffiti with a high pressure cleaner at 70 bar at a temperature of 70 ° Celsius.
- Re-protect with two coatings of Pica Protector 500.

Solution to be used:

Concentrate (pH 8,5).

Estimated amount to be used:

Varies according to the surface. In General estimate the following;

Painted surfaces, natural stone	0,20L/m ²
Concrete, Brick	0,30L/m ²
Render	0,40L/m ²

Personal protective measures:

Not needed.

Labelling:

Se MSDS

Storage/durability:

Store dark and frost free. Durability, about 24 months in sealed original container.

Technical data:

Contains:	Montan waxes
Appearance:	Milky white liquid
Odour:	Neutral

The information supplied is only intended to be used as a guideline. Pica Kemi AB therefore accepts no liability based on this information on behalf of the user.

Pica AB
Kabingatan 13, S-212 39 MALMÖ
Tel. +46-40-18 58 20 Fax.+46-40-18 58 23
Hemsida: www.picakemi.se